



Datum	artikelnummer
06/12/2022	108020

Cuore WAP 1000

Description

Cuore WAP 1000 is a water soluble primer, consisting of styrene and acrylate polymer. The colour is milky white during application, becoming glossy after drying. The concentrated primer requires mixing with water before application to the surface. It has a good penetration power and ensures good surface adhesion.

Benefits

Concentrated primer, diluted with water.

Can be used as primer on many different surfaces.

Good penetration power.

Improves surface adhesion.

Range of use

WAP 1000 is used for pre-treating surfaces before applying cement-based products such as liquid mortars, putties, liquid anhydrite, etc. The primer is typically used on top of concrete, concrete elements, putties, liquid mortars, wood, tiles, etc. and it improves the adhesion between the underlying surface and the top layer. Because of its good film formation on the surface, the primer also prevents excess extraction of the mixing water in the subsequent product (e.g. liquid mortar).

Preparation

The surface must be well-suited, firm and free from any loose particles, cement slurry, dust or other impurities that could prevent sufficient adhesion to the surface. For the primer's film formation, the temperature of the underlying surface must not be below +5°C. The best results are achieved when the temperature in the room is between +10°C and +25°C.

Application

WAP 1000 is applied, diluted, to the surface using a primer sprayer, watering can, broom or paint roller and is then swept/brushed thoroughly down into the surface. Avoid the formation of puddles. When working with WAP 1000, use rubber gloves and protective goggles for your own protection. Adequate ventilation is also important.

Limitations

The primer must not be used at temperatures below +5°C.

Cleaning

Sprayers, brooms, paint rollers, tools and other materials must be cleaned with water immediately after use. Dried primer can be difficult to dissolve/remove.

Datum	artikelnummer
06/12/2022	108020

Product information

Surface	Mixing ratios		Use concentration	
	primer	water	L/m ²	M ² /L
Non-absorbent	1	1	0.15	7
Normal absorption	1	3	0.10	10
Strong absorption	1	6	0.20	5
2 time	1	3		
Wood	5	1	0.20	5
Tiles/stone	1	1	0.15	7

Onze adviezen met betrekking tot de technische toepassing in woord, geschrift of door middel van proeven, worden naar beste weten verstrekt, doch gelden slechts als vrijblijvende aanwijzingen, ook ten aanzien van eventueel beschermende rechten van derden. Zij ontslaan u niet van de verplichting, de door ons geleverde producten op hun geschiktheid voor de beoogde procedures en doeleinden te controleren. Toepassing, gebruik en verwerking van de producten vinden plaats buiten onze controlemogelijkheden. Zij vallen derhalve onder uw eigen verantwoordelijkheid. In geval van eigen aansprakelijkheid blijft deze, voor alle schadegevallen, beperkt tot de waarde van de door ons geleverde en door u gebruikte goederen. Vanzelfsprekend garanderen wij u de goede kwaliteit van onze producten, e.e.a. volgens de in onze algemene verkoop- en leveringsvoorwaarden genoemde maatstaven.